

## Verti-Drain® 2220

The robust Verti-Drain® 2220 is a high speed unit, capable of handling a 24mm / 1" diameter tine and working to depths of 22cm / 9". Thanks to its heavy duty construction, the 2220 is ideal for a range of creation applications where durability and speed is key.

### Specifications

SKU	111.122.020
Operation	Tractor Mounted
Working width (m)	2.08
Working width (inch)	82
Max. Working depth (mm)	225
Max. Working depth (inch)	9
Working speed at hole spacing 65 mm (km h)	1.79
Working speed at hole spacing 21.2 inch (mph)	1.1
Weight (kg)	1155
Weight (lbs)	2541
Hole distance with 12 mm tines (mm)	65
Hole distance with 1.2 x 6 inch tines (inch)	2.5
Hole distance with 18 mm tines (mm)	130
Hole distance with 3.4 x 9 inch tines (inch)	5.12
Hole spacing distance driving direction (mm)	25 - 195
Hole spacing distance driving direction (inch)	1 - 7.5
Max. Diameter solid tine (mm)	24 x 225
Max. Diameter solid tine (inch)	1 x 9
Max. Diameter hollow tine (mm)	25 x 225
Max. Diameter hollow tine (inch)	1 x 9
Min. Tractor HP required	50
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	1300
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	2866
Max. capacity with spacing 65 mm (m <sup>2</sup> hr)	3728
Max. capacity with spacing 21.2 inch (ft <sup>2</sup> hr)	40128
Three-point hitch	3-Point CAT 1/2
Rpm Max.	540
Gearbox oil	80W90 5.5 liter
Lubricant	EP 2
Dimensions (width mm)	2220
Dimensions (height mm)	900
Dimensions (length mm)	1210
Dimensions (width inch)	87.4
Dimensions (height inch)	35.4
Dimensions (length inch)	47.6
Slip clutch setting	550 NM (4868 lbf-in)