



ER406 QUOTATION SHEET

TO:

PLACE OF DELIVERY: Kaltbrunn

WARRANTY: 1 Year(since the date that buyer receive the machine)

PACKING WAY: 4Units in 1*40HQ ,3 Units in 1*20GP Container

TERMS OF PAYMENT: 100% paid by T/T.

MODEL	DESCRIPTION	U-P (FOB Kaltbrunn)	QTY	AMOUNT
ER406	Italy Hydrostatic Driving system, Yanmar 3TNV88-BSSY Engine, American Eaton Pump, Standard Bucket, Quick Hitch, 26*12-12 Agricultural tyres, Seat, Adjustable Steering Wheel, Lock for Lifting and Steering Cylinder, Tipping Cabin, Electrical Joystick, Floating Function, Pressure Checking System.	21890.00 Alles in CHF. inkl. MwSt.	1	
OPTIONS	Cabin	1600.00		

Picture I



Picture II





Options:

E4 Lamp	175.00	3 Point Hitch	525.00
LED Working Light	175.00	Varta Anti-Freeze Battery	120.00
LED Alarm Light	30.00	Loader Damper	305.00
Extra Hydraulic Line	165.00	Bobcat Quick Hitch	75.00
Trailer Ball	60.00	Euro Quick Hitch	0.00
Extra Electric Line	20.00	Trima Quick Hitch	0.00
26*12.00-12 Grass Tires	0.00	Perkins403D-11 engine(euro3)	480.00
Yanmar 3TNV388-BBSY(Tier4)	1900.00	Closed cabin	650.00
Kohler 1003 engine (Euro5)	0.00	Kobuta D1105-E4B (Euro5)	0.00
Xinchai 3B11 18.5kw (Euro5)	-300.00		

Attachments:

Pallet Forks	700.00	Snow Blade	1280.00
Adjustable Pallet Forks	1210.00	V-Snow Blade	1400.00
Grapple Forks	1230.00	Crops Blade	1250.00
European Grapple Forks	1410.00	Bale Grab	1400.00
Wooden Forks	1300.00	Drum Folder	1000.00
Manure Forks	680.00	Sweeper	2000.00
Grapple Bucket	1330.00	Sweeper With Collector	2100.00
4 In 1 Bucket	1300.00	Auger(400mm)	1900.00
Light Bucket	1030.00	Flail Mower	1740.00
Snow Bucket	1000.00	Digger	1400.00
Snow Bucket With Wings	1420.00	Digger With Thumb	1420.00
Mixer Bucket	1450.00	Jib	900.00
Rock Bucket	1130.00	Hay Forks(One Fork)	770.00
Crops Bucket(1.6m3)	1130.00	Hay Forks(Two Forks)	840.00
Salt Spreader	1200.00	Double-Blade Bucket	870.00

Specifications:

1.0 Engine Details	
(1) Model:	3TNV88-BSSY Engine
(2) Rated Power:	20.7KW
(3) Rated Speed:	2400r/min(rpm)
(4)Fuel Consumption Ration in Standard Working Condition:	252g/kw.h



2.0 Operating Specifications

(1) Bucket Capacity:	0.26m ³
(2) Loading Capacity	600 KG
(3) Operation Weight:	1700KG
(4) Lifting Time:	≤8.0s
(5) Driving Speed:	0-6.9km/h
(6)Min.Turning Radius:	2450mm
(7) Max.Turning Angle:	±35°

3.0 Overall Dimensions

(1) Overall length(bucket on ground)	3673mm
(2) Overall Height:	2250mm
(3) Overall width:	1200mm/1060mm
(4) Dumping Height:	1870mm
(5) Dumping Reach:	800mm
(6) Min.Ground Clearance:	220mm
(7) Wheel Base:	890mm

4.0 Brake System

(1) Service Brake:	Four wheel hydraulic spread-shoed brake
--------------------	---

5.0 Tyre

26*12-12 Agricultural tires(1200mm wide) or 27*8.5-15(1060mm wide)

